



MATERIAL SAFETY DATA SHEET

MSDS019

SECTION I - PRODUCTION IDENTIFICATION

300, 600 & 800 ALUMINIZED ZETEX FABRIC

MANUFACTURER:

NEWTEX INDUSTRIES, INC.
8050 Victor-Mendon Road
Victor, New York 14564

SECTION II - HAZARDOUS INGREDIENTS

The above products are considered "articles" according to OSHA hazard Communication Standard 29 CFR 1910.1200 and, as such, are exempt from the Material Safety Data Sheet provisions of 29 CFR 1910.1200(G)(6). As a service to the customer, Newtex Industries Inc. has prepared this Material Safety Data Sheet to provide appropriate safety and handling information. These products are considered non-hazardous when used according to accepted practices for the intended use.

<u>AS MANUFACTURED:</u>	<u>WT. %</u>	<u>TLV/PEL</u>
Continuous Fibrous Glass (CAS # 65997-17-3)	88.30%	Not Listed
Total dust		ACGIH TLV : 10 mg/m3 OSHA PEL : 15 mg/m3
Respirable dust		OSHA PEL : 5 mg/m3
Aluminized Polyester Film	1.23%	:10 mg/m3
Acrylonitrile Elastomer	3.69%	:10 mg/m3
Polychloroprene Elastomer	3.18%	:4 mg/m3
Chlorine	1.92%	:3 mg/m3
Antimony Trioxide	0.72%	:0.5 mg/m3
Red Lead	0.64%	:0.15 mg/m3

Newtex Industries, Inc. Main Office: 8050 Victor-Mendon Rd., Victor, NY 14564-9109, Phone (585) 924-9135, Fax (585) 924-4645
E-Mail: sales@newtex.com; Internet address: www.newtex.com

Revision #
Last Modified on
Approved by Scott Gregorio

MATERIAL SAFETY DATA SHEET**MSDS019**

SECTION III - PHYSICAL DATA

BOILING POINT : N/A SPECIFIC GRAVITY RANGE(H₂O=1) : N/A
MELTING POINT : 400 F PERCENT VOLATILE BY VOLUME : N/A
VAPOR PRESSURE(mm Hg) : N/A EVAPORATION RATE(Butyl Acetate=1) : N/A
VAPOR DENSITY(Air=1) : N/A SOLUBILITY IN WATER : Insoluble
APPEARANCE AND ODOR : Fabric that is tan/white on one side and aluminum on the other
with a clean odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED) : N/A
FLAMMABLE LIMIT : LEL: N/A UEL: N/A
UNUSUAL FIRE AND EXPLOSIVE HAZARDS : N/A
SPECIAL FIRE FIGHTING PROCEDURES : N/A
EXTINGUISHING MEDIA : Tends to be self-extinguishing. Starts to decompose at about 400 degrees F. Aluminized polyester film starts to melt at about 400 degrees F. Extinguish with water and/or smother. The adhesive system is self – extinguishing and tends to smother flame.

SECTION V - HEALTH HAZARD DATA

ROUTES OF ENTRY : This material will not enter the body during normal use.
CARCINOGENICITY : This product is not known as a carcinogen.
HEALTH HAZARD(Acute & Chronic) : None known
SIGNS AND SYMPTOMS OF EXPOSURE : None known
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE : None known
EMERGENCY FIRST AID PROCEDURES :
Skin : Wash thoroughly with soap and water after handling material.
Eyes : Wash with water.

MATERIAL SAFETY DATA SHEET**MSDS019**

SECTION VI - REACTIVITY DATA

STABILITY : Stable at room temperature. At elevated temperatures, range unknown, decomposition may occur.

CONDITIONS TO AVOID : High temperatures in enclosed areas.

INCOMPATIBILITY : N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS : At high Temperature, chlorine and antimony fumes are possible. Tends to smother in a flame.

HAZARDOUS POLYMERIZATION : Will not Occur

CONDITIONS TO AVOID : High Temperature in enclosed areas.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Material is a solid.

Pick up big pieces and sweep up any scrapes.

WASTE DISPOSAL METHOD : Burial in a Federal or State approved landfill.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING : None known

OTHER PRECAUTIONS : None known

SECTION VIII - CONTROL MEASURES

RESPIRATOR PROTECTION (specify type): Wear a dust mask if excessive dust is generated.

VENTILATION

LOCAL EXHAUST : None

SPECIAL : None

MECHANICAL : None

OTHER : None

PROTECTIVE GLOVES : None

EYE PROTECTION : None

OTHER PROTECTIVE CLOTHING OR EQUIPMENT : Wear safety eye wear

WORK HYGIENIC PRACTICES : Wash thoroughly with soap and water after handling of the material.

* The information herein is given in good faith, but no warranty, expressed or implied is made and we assume no liability from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.

The employment policy of Newtex Industries, Inc. is to provide equal opportunity to all persons. Our company, therefore, has made a commitment to equal employment opportunity through a positive and continuing Affirmative Action Program. No employee or applicant for employment will be discriminated against because of race, color, religion, sex, national origin, age, disability, veteran status or any other Federal or State legally-protected classes.

Newtex Industries, Inc. Main Office: 8050 Victor-Mendon Rd., Victor, NY 14564-9109, Phone (585) 924-9135, Fax (585) 924-4645

E-Mail: sales@newtex.com; Internet address: www.newtex.com

Revision #

Last Modified on

Approved by Scott Gregorio

Page 3 of 4



MATERIAL SAFETY DATA SHEET

MSDS019

Newtex Industries, Inc. Main Office: 8050 Victor-Mendon Rd., Victor, NY 14564-9109, Phone (585) 924-9135, Fax (585) 924-4645
E-Mail: sales@newtex.com; Internet address: www.newtex.com

Revision #
Last Modified on
Approved by Scott Gregorio

Page 4 of 4