



ASBESTOS-FREE PROTECTION WITH EXTRA PERFORMANCE

S006

PRODUCT SPECIFICATION
STYLE 1000
ZETEXPLUS

GENERAL DESCRIPTION: 1000 ZP fabric is made from highly texturized silica yarn and has a proprietary high temperature treatment.

APPLICATIONS: Typical applications include high temperature expansion joints, curtains, blankets, and drop cloths for light to medium industrial applications.

Typical industries include thermal and nuclear power plants, refineries and petro-chemical industries, filtration, steel, aluminum, copper and other basic metal industries, turbine insulation, heat treating, stress relieving, automotive and industrial maintenance.

PHYSICAL PROPERTIES:

Weight:	33 Oz./Square Yard
Construction: Warp x Fill	20 x 7
Weave:	Plain
Thickness:	0.065"
Temperature	Continuous temperatures to 1500°F (815°C) and 2000°F (1093°C) for short durations.
*K Factor (Heat Conductivity):	0.3399 BTU/inch/hr/sq ft/°F

CHEMICAL RESISTANCE: Resists most acids, alkalis and solvents, with the exception of hydrofluoric acid and corrosive environments at elevated temperatures.

AVAILABLE TREATMENT: Proprietary high temperature treatment, which provides outstanding abrasion and better molten metal splash resistance, is standard. This treatment improves the ability to cut, sew, handle the product, and significantly reduces airborne fibers and unraveling. Other colors available upon request.

ORDERING INFORMATION:

Standard Width:	40" - 60"
Length of Roll:	50 Yards

* For base fabric

Revision # 2
Last Modified on 9/24/03 1:30 PM
Approved by Suresh Deshpande