



ASBESTOS-FREE PROTECTION WITH EXTRA PERFORMANCE

S009

PRODUCT SPECIFICATION
STYLE 1085 S/S
SILVER SILICONE

GENERAL DESCRIPTION: ZETEX Style 1085 S/S, is a satin weave fiberglass fabric coated with silicone rubber. The high temperature, flame retardant silicone rubber provides temperature resistance up to 500°F and the heavy duty 1085 S/S provides maximum resistance to flex, tear, abrasion and puncture. ZETEX Style 1085 S/S provides water, oil and chemical resistance; generates little or no smoke, and is easily sewn or fabricated.

APPLICATIONS: Heavy-duty fabric suitable for molten metal splash protection in welding curtains, blankets, other types of equipment protection covers and shields. It can also be used in removable insulation pads, expansion joints, and flange covers.

PHYSICAL PROPERTIES:

| | |
|---|---|
| Color - Coating: | Silver - Silicone |
| Weight: | 32.0 Oz./Square Yard |
| Thickness: | 0.035" |
| Flame Resistance: | Flame out (sec) 5 sec. max. Afterglow (sec) 10 sec. max. Char length (in) 1" max. |
| Tensile Strength: lbs./inch FED STD 191/5102 | Warp – 275 lbs. Fill – 250 lbs. |
| Tear Strength: lbs. FED STD 191/5136 | Warp - 65 lbs. (min.) Fill - 55 lbs. (min.) |
| Mullen Burst, PSI: ASTM-D-774 | 750 PSI minimum |
| Temperature Resistance: | -65°F to 500°F |

ORDERING INFORMATION:

| | |
|-----------------|----------|
| Length of Roll: | 50 Yards |
|-----------------|----------|

Revision # 3
Last Modified on 01/23/04 3:00 PM
Approved by Suresh Deshpande

NEWTEX INDUSTRIES, INC.

8050 Victor-Mendon Road, Victor, NY 14564-9109 • Phone: 585-924-9135, 800-836-1001 • Fax: 585-924-4645
34016 Ninth Ave. So. Bldg. D, Suite 3, Federal way, WA 98003 • Phone: 253-838-7760 • Fax: 253-838-5603