



ASBESTOS-FREE PROTECTION WITH EXTRA PERFORMANCE

S024

PRODUCT SPECIFICATION
STYLE 1200 W/W
Z-TEMP

GENERAL DESCRIPTION: ZETEX 1200 W/W Z-TEMP fabric is manufactured from highly texturized amorphous silica yarns and is coated with aluminum pigment. The fabric is reinforced in both warp and fill directions with Type 304 stainless steel wire 0.0045" in diameter.

PHYSICAL PROPERTIES:

Weight:	38 Oz./Square Yard
Construction: Warp x Fill	(10 +5) x 7(2)
Weave:	Plain
Thickness:	0.075"
Min. Breaking Strength:	Warp - 475 lbs. Fill - 350 lbs.
Taber Abrasion: CS-10 wheels 1000 gm load	700+ cycles
*Temperature:	Continuous temperatures to 1100°F (593°C) and higher temperatures for short duration.
*K Factor (Heat Conductivity):	0.3399 BTU/inch/hr/sq. ft/°F

***CHEMICAL RESISTANCE:** Resists most acids, alkalies and solvents, with the exception of hydrofluoric acid and corrosive environments at elevated temperatures.

ORDERING INFORMATION:

Length of Roll:	50 Yards
-----------------	----------

*For basic fabric

Revision # 1
Last Modified on 12/11/03 11:45 PM
Approved by Suresh Deshpande