



ASBESTOS-FREE PROTECTION WITH EXTRA PERFORMANCE

**S048**

PRODUCT SPECIFICATION  
STYLE 2200  
ZETEXPLUS

**GENERAL DESCRIPTION:** 2200 ZP fabric is made from highly texturized amorphous silica yarn and has a proprietary high temperature treatment.

**APPLICATIONS:** Typical applications include high temperature expansion joints, curtains, blankets, and drop cloths for medium to heavy industrial applications, flue ducts, turbine insulations, and gasketing. Typical industries include thermal and nuclear power plants, refineries and petro-chemical industries, filtration, steel, aluminum, copper and other basic metal groups, construction industry, chemical processing plants, petroleum refineries, heat treating and stress relieving, automotive, and industrial maintenance.

**PHYSICAL PROPERTIES:**

Weight:	68 Oz./Square Yard
Construction: Warp x Fill	10 X 7
*Thickness:	.125"
Weave:	Plain
*K Factor:	0.3385
Temperature:	Continuous temperatures to 1500°F (815°C) and up to 2000°F (1093°C) for short duration.

**CHEMICAL RESISTANCE:** Resists most acids, alkalis and solvents, with the exception of hydrofluoric acid and corrosive environments at elevated temperatures.

**AVAILABLE TREATMENT:** Proprietary high temperature treatment, which provides outstanding abrasion and better molten metal splash resistance, is standard. This treatment improves the ability to cut, sew, handle the product, and significantly reduces airborne fibers and unraveling. Other treatments available upon request.

**ORDERING INFORMATION:**

Length of Roll:	50 Yards
Standard Width:	40" - 60"

\* For base fabric

Revision # 1  
Last Modified on 12/15/03 1:15 PM  
Approved by Suresh Deshpande