



ASBESTOS-FREE PROTECTION WITH EXTRA PERFORMANCE

S077

PRODUCT SPECIFICATION
STYLE 500
SILVER SILICONE

GENERAL DESCRIPTION: ZETEX 500 S/S, satin weave, is a fiberglass fabric coated with silver silicone rubber. It has high resistance to heat (temperatures up to 500°F), abrasion, flexing, tear and puncture. ZETEX style 500 S/S is silver in color, provides water, oil and chemical resistance, generates little smoke and is easily sewn or fabricated.

APPLICATIONS: Removable insulation pads, protective flange shields and equipment covers, welding curtains, and expansion joints.

PHYSICAL PROPERTIES:

Color - Coating:	Silver - Silicone
Weight:	15.0 Oz./Square Yard
Thickness:	.015"
Flame Resistance: FED STD 191/5903.2	Flame out (sec) 1 sec. max. Afterglow (sec) 1 sec. max. Char length (in) 1/16" max.
Tensile Strength: lbs./inch FED STD 191/5102	Warp - 200 lbs. Fill - 150 lbs.
Tear Strength: lbs. FED STD 191/5136	Warp - 50 lbs. (min.) Fill - 40 lbs. (min.)
Mullen Burst, PSI: ASTM-D-774	400 PSI minimum

ORDERING INFORMATION:

Length of Roll:	50 Yards
-----------------	----------

Revision # 1
Last Modified on 12/17/03 10:45 AM
Approved by Suresh Deshpande