



ASBESTOS-FREE PROTECTION WITH EXTRA PERFORMANCE

S101

PRODUCT SPECIFICATION
STYLE 617-2
PTFE (2 SIDES)

GENERAL DESCRIPTION: Newtex Style 617-2 PTFE is a fluorocarbon coated fiberglass fabric designed for use in removable blankets as a weather/chemical resistant barrier. This fabric is easily sewn and is flexible enough to conform to intricate shapes.

APPLICATIONS: Removable blankets for valves, flanges, pumps, instrumentation and freeze protection.

ADVANTAGES: Low flammability, good chemical resistance, excellent cleanability, excellent abrasion resistance and minimal smoke levels.

PHYSICAL PROPERTIES:

Weight:	18.0 Oz./Square Yard Nominal
Weave:	Satin Weave
Thickness:	.017"
Service Temperature:	-67°F to +550°F
Breaking Strength:	Warp - 410 lbs./in. avg. Fill - 375 lbs./in. avg.
Tear:	Warp - 20 lbs. min. avg. Fill - 20 lbs. min. avg.
Flammability:	V-O Rating UL 94 Vertical burning test
Color:	Gray
Chemical Resistance:	The fluorocarbon coating is extremely resistant to most industrial chemicals and has been used in applications to 500°F.

ORDERING INFORMATION:

Length of Roll:	50 Yards
-----------------	----------

Revision # 1
Last Modified on 12/18/03 12:30 PM
Approved by Suresh Deshpande