



ASBESTOS-FREE PROTECTION WITH EXTRA PERFORMANCE

S216

PRODUCT SPECIFICATION
STYLE 475 AND 407
SALMON

GENERAL DESCRIPTION: ZETEX Salmon 475 and 407 fabrics are woven using continuous filament, amorphous silica yarns and are coated with a proprietary treatment.

<u>PHYSICAL PROPERTIES:</u>	<u>475 fabric</u>	<u>407 fabric</u>
Weight:	15.5 oz./yd ²	16.0 oz/yd ²
Construction:	28 X 20	48 X 32
Weave:	Plain	4 Harness Satin
Thickness:	0.017"	0.018"
Width:	38" or 60"	61"
Tensile Strength:	Warp - 500 lbs./in. Fill - 350 lbs.	Warp - 340 lbs. Fill - 250 lbs./in.
Tear Strength:	Warp - 35 lbs. Fill - 30 lbs.	Warp - 50 lbs. Fill - 45 lbs.
Color:	Salmon or Black (other colors available upon request)	
Flame Resistance: FED STD 191/5903.2	Flame out (sec) 1 sec. max. Afterglow (sec) 1 sec. max. Char length (in) 0.5" max.	
*Temperature:	Continuous temperatures to 1000°F (538°C) and higher temperatures for short duration.	

CHEMICAL RESISTANCE: Base fabric resists most acids, alkalies and solvents, with the exception of hydrofluoric acid and corrosive environments at elevated temperatures.

ORDERING INFORMATION:

Length of Roll: 50 Yards

* For base fabric

Revision # 5
Last Modified on 10/08/2004 8:30 AM
Approved by Suresh Deshpande